

7401 Mesa Road, Houston, TX 77028 1.800.390.2752 www.premierdrillpipe.com

JT7020^{*}

Premier horizontal directional drill rod is a premium manufactured product. We start with 4137H extra wear-resistant bar stock and heat treat the tool joints to oilfield API S135 specifications for ultimate fatigue resistance. The tool joints are machined to exact specifications and matched with precision fabricated tube bodies. The tubes are cut to length from a 4100 alloy series, high chromemoly seamless tube and are forged, heat treated and machined to compliment the tool joints. The components are then inertia welded, producing an uncompromisable weld. This process is the exact same which is used throughout the world for oilfield drill pipe manufacturing. The rod is then MAG particle inspected to ensure the integrity of the weld. It is because of our attention to detail that our rods can be used with confidence as it is subjected to the combined loads of pull/thrust, bending and torque produced from the drill rig.

.00*

General	1	
HDD Compatibility:	Ditch W	itch JT7020/JT8020/JT1
Thread Form:	V-0.038	R
Dimensions:	U.S.	Metric
Tube OD (in, mm)	3.500	88.9
Tube WT (in, mm)	0.368	9.3
Tool Joint OD (in, mm)	4.000	101.6
Tool Joint ID (in, mm)	1.500	38.1
Rod Length (ft, m)	15	4.918
Weights	U.S.	Metric
Rod (lb per rod, kg per rod)	230	104.3
Performance	U.S.	Metric
Bend Radius**, min. (ft, m)	193	63.2
Bending Ratio**, max. (° per rod)	4.5	
Built Ratio**, max. (% slope per roo	d) 7.8	
Yield Torque (ft-lb, N-m)	14,451	19,593
Make-up Torque (ft-lb, N-m)	8,671	11,756
Tensile Strength (lb, N)	488,825	2,174,400



*Ditch Witch & JT7020, JT8020, JT100 are trademarks of Charles Machine Works.

** Bend limits are valid only for pure bending (no other loads acting at the same time, e.g. Push/Pullback, etc).

Note: The information provided here is general data. This data is not a warranty or quality certificate. Premier Drill Products LLC retains the right to change this data at any time for product improvement.

©2017 Premier Drill Products, LLC.